VENUS LED 10W SURFACE EMERGENCY LIGHT

Emled-110NM SURFACE











Features and Application

- New high lumens self-contained LED emergency light for surface installation.
- Suitable for various indoor environments such as retail, commercial, hospitality and healthcare industries.
- LED lamps provide high efficiency, durability and low energy consumption.

Technical Data

Mode of Operation Non-maintained

Samsung 10W High flux white LED

Operating Temperature ta 0°C ~ 50°C

230V AC 50Hz/60Hz Mains Supply

Power Consumption

Battery High temperature NIMH battery

Fully automatic Charger

Green LED Charging Monitor

Recharge Period 24 hours

Test-switch for independent testing Testing Facility

Emergency Duration

Low-voltage cut-off to prevent over-Safety Feature

discharge of battery

Disc: Polycarbonate Construction

Surface: Aluminium casing with

epoxy powder coating

Surface mount


Weight (Nett/Gross) 0.82 kg / 0.92 kg


SS 563-2:2010/A1:2013 SS IEC 60598-2-22:2016 Compliance SS IEC 60598-1:2016

IP 20 IP Rating Warranty 1 year

Installation

Dimensions (mm)





Ordering Information

MODEL	LAMP
EmLED-110NM SURFACE	Samsung 10W High flux white LED